

*CSH series*  
*Multi Cartridge Sanitary Housings*  
*3 Through 21 Round*

Critical Process Filtration, Inc.® • One Chestnut Street • Nashua, NH • 03060  
Telephone: 603-880-4420 Fax: 603-880-4536

CSH multi cartridge sanitary housings, available in 3,6,8,12 and 21 round models with swing bolt closures are a proven design suited for high purity beverage, chemical and pharmaceutical applications. They are manufactured in 316L Stainless Steel with a 25 RA internal finish. All CSH housings are standard with 2-226 style cartridge adaptors with removable tube sheet, giving you a positive locking tab seal. This allows flexibility in one housing to use different cartridge lengths and maximize filter performance and cost. CSH housings have no internal threaded parts that come in contact with the process fluid each housing is standard with a spring loaded hold down plate and are standard with food grade silicone gaskets. 1" sanitary gauge port tops with 1/2" sanitary vent and drain ferrules are standard features. Each vent and drain port is standard with solid cap, silicone gasket and clamp.



Maximum Operating Parameters

Maximum Pressure: ..... 150 PSI (10 bar)  
Maximum Operating Temperature: ..... 230°F (110°C)

Dimensions

Complete and detailed line drawings are available upon request. Please contact Critical Process Filtration with the model number and specifications you require.

Standard Specifications

This is to give you an overview of our standard product, please see reverse for options and ordering information.

Model	Number Round	Length of Cartridge	Inlet / Outlet	Drains	Gauge Port With Vent	Max Ctg Diameter	Gaskets	Mounting Legs	Cartridge Seal 2-226 / Tabs
CSH32	3	20"	2" TC	1/2" TC	1" TC / 1/2" TC	2 3/4"	Silicone	Yes	Yes
CSH33	3	30"	2" TC	1/2" TC	1" TC / 1/2" TC	2 3/4"	Silicone	Yes	Yes
CSH34	3	40"	2" TC	1/2" TC	1" TC / 1/2" TC	2 3/4"	Silicone	Yes	Yes
CSH63	6	30"	2" TC	1/2" TC	1" TC / 1/2" TC	2 3/4"	Silicone	Yes	Yes
CSH64	6	40"	2" TC	1/2" TC	1" TC / 1/2" TC	2 3/4"	Silicone	Yes	Yes
CSH83	8	30"	2" TC	1/2" TC	1" TC / 1/2" TC	2 3/4"	Silicone	Yes	Yes
CSH84	8	40"	2" TC	1/2" TC	1" TC / 1/2" TC	2 3/4"	Silicone	Yes	Yes
CSH123	12	30"	3" TC	1/2" TC	1" TC / 1/2" TC	2 3/4"	Silicone	Yes	Yes
CSH124	12	40"	3" TC	1/2" TC	1" TC / 1/2" TC	2 3/4"	Silicone	Yes	Yes
CSH213	21	30"	4" TC	1/2" TC	1" TC / 1/2" TC	2 3/4"	Silicone	Yes	Yes
CSH214	21	40"	4" TC	1/2" TC	1" TC / 1/2" TC	2 3/4"	Silicone	Yes	Yes

Vent & Drain Twist Valve Option



Hold Down Plate / Removable Tube Sheet



Total Performance

Critical Process Filtration, Inc.® is a vertically integrated supplier of filtration products and services to industries in which filtration is considered to be a critical part of the manufacturing process. We manufacture a complete line of products to help you achieve all your filtration requirements from a single source.




NOTE

Please contact Critical Process Filtration for other options or special requirements.

Ordering Information

The housing catalog number is made up of several variable characters i.e. number round, length, cartridge style, gasket material and others below. For example: a 3 round, 30" length, swing bolt closure, 316L SS, 2-226 seal, 2" ferrules, welded legs, 25 RA internal finish with Silicone gasket would be designated as: CSH33S6B21AS



Telephone: 603-880-4420  
 Fax: 603-880-4536  
 Web Site: www.criticalprocess.com  
 E-mail: sales@criticalprocess.com